

Electrobombas sumergidas línea achique / Submerged Electric-pump dwarf line

• Serie práctica / Practical series

Modelo Model	Código Code	C.V. H.P.	Amp. 200II Amp. 220 II	Imp. Imp.	Rendimientos Yields						Peso Kg Peso Kg	
AN-1-M	012000	0,3	2,1	1"	l/h	1.800	3.600	5.400				2,8
					Hm	5	3	0,5				
AN-3-M	012002	0,4	2,2	1,1/4"	l/h	900	5.000	7.000	8.300			4,2
					HM	7	5	3	0,5			
AN-5-M	012004	0,5	3,1	1,1/4"	l/h	2.700	6.600	10.800	13.800	15.000	15.500	5,2
					Hm	10	8	6	4	2	1	

Características:

Electrobombas sumergidas para aguas limpias o ligeramente cargadas.

Serie AN-1. Construidas con carcasa externa en polipropileno. Temperatura media del agua 35° C. Serie AN-3 y 5. Cuerpo de bomba, carcasa motor y eje en acero inoxidable. Turbina y difusor noril. Motores asíncronos de dos polos en baño de aceite, en los monofásicos, condensador incorporado.

Charascteristics:

Electric-pump submerged for clear water or slightly laden.

Serie An-1.They are built with external carcass in polipropileno. Half temperature of the water 35° C.

Serie AN-3 and 5. Pump body, motor carcass, shaft in turbine stainless steel and noril diffuser.

Serie AN-8-10 and 15. Construction in smelting grey. Engines asynchronous of two poles in oil bath, the monophases incorporate condensing



• Interruptor automático de nivel / Float switch

Modelo Model	Código Code	Llenado o vaciado por inversión	Full or empty by investment
IN-5	012050		
IN-7	012054		

