



• **Línea aqualine / Aqualine line**

Modelo Model	Código Code	C.V. C.V.	Amp. 200II Amp. 220 II	Ø Imp. Ø Imp.	Rendimiento Yields										Largo Long	Peso Kg Weight Kg
					L/m	10	25	50	58	68	75	85	97	105		
					m³/h		1,5	3	3,5	4	4,5	5,1	5,8	6,3		
					Altura en metros / Height in meters											
AQUALINE 40	2200	0,8	4,1	1 1/4"	40	32	24	19	16	13	9	4			470	12
AQUALINE 60	2202	1,2	6	1 1/4"	60	50	40	35	30	25	20	10	2		540	13
AQUALINE 80	2204	1,6	8	1 1/4"	80	68	55	47	45	38	30	20	2		620	15

Características:

Electrobomba sumergible multiturbina idóneas para bombeo de aguas limpias. Construidas en acero inoxidable, turbina y difusor Noryl GFN. Cierre mecánico en carburo de silicio, que permite aguas con contenido de arenas. Motor con estátor encamisado, refrigerado mediante la misma agua bombeada, permitiendo inmersión hasta 20 m. Ø bomba 127 mm.

Sobre pedido interruptor automático de nivel.

Characteristic:

Submersible electric-pump multi-impeller suitable for the pumping of clear water. It's built in stainless steel, impeller and diffuser noryl GFN. Mechanical shuter in silicon carbide that permits water with sands content. Motor with stator concealing, refrigerated through the same pumped water, permitting dip until 20 meters. Pump 127mm.

On demande, they can be supplied with float switch.