Electrobombas centrífugas Línea monobloc / *Centrifugal Electric-pumps monobloc line*

Modelo *Model*	Código *Code*	C.V. *H.P.*	Amp. / *Amp 3x380V*	Caudal m³/h *Wealth m³/h*																																Peso Kg. *Weight Kg.*
				6	7,5	9	12	15	18	21	24	27	30	33	36	39	42	48	54	60	66	72	78	84	96	108	120	132	144	156	168	180	195	210	225	240	
				Altura manométrica m.c.a. / *Manometric headat the bowl*																																		
U 32-160B	015002	3	5,5	28,2	28	27,3	25,7	23,8	21,4	18,5	14,8																									39
U 32-160A	015100	4	7,1	36,4	36	35,4	34,2	32,8	31,1	28,8	26	22,3																								42
U 32-200C	015004	5,5	9,4	40	39,5	38,8	37,5	36	34,2	32,2	30	27																								51
U 32-200B	015102	7,5	14,2	52	51,5	51	50	48,5	46,8	45	42,7	40,1	37	33,3	28,7																					63
U 32-200A	015006	10	16,5	60,5	60	59,5	58,5	57,2	55,5	53,7	51,5	49	46,2	42,7	38,5																					69
U 32-250C	015104	12,5	20,1		68,5	68	67	66,5	63,5	61,5	58,7	55	50,5																							83
U 32-250B	015008	15	24,2		81	80,5	79,5	78,5	77	75	72,6	70	66,5																							90
U 32-250A	015106	20	30,1		92,5	92	91,5	90,5	89,5	88	85,7	83,5	80																							120
N 40-125B	015010	3	5,2			21,3	21,2	21	20,6	20,1	19,4	18,7	17,9	17																						37
N 40-125A	015108	4	7,1			25,8	25,8	25,6	25,4	24,9	24,4	23,7	22,9	22	21,1																					40
N 40-160B	015012	4	7,4			30,1	30	29,6	29	28,2	27,1	25,9	24,4	22,8	21																					47
N 40-160A	015110	5,5	9,9			35,6	35,5	35,3	35	34,2	33,2	32	30,6	29	27,3	25,4																				50
N 40-200B	015014	7,5	13,2			47	46,8	46,4	45,6	44,5	43,2	41,6	39,9	37,9	35,8	33,4																				65
N 40-200A	015112	10	16,8			58,8	58	57,9	57,6	56,9	56	54,7	53	51,1	48,9	46,5	43,9																			71
N 40-250B	015016	15	24,2			74,6	74,2	73,5	72,7	71,7	70,4	69	67,2	65	62,5	59,5	56																			91
N 40-250A	015114	20	32			90,4	89,8	89,3	88,5	87,5	86,6	85,5	84	82,5	80,5	78,5	76																			121
I 50-125B	015018	4	7,4				20,2	20,2	20,1	20	19,8	19,3	19,1	18,7	18,3	17,8	17,4	16,4	15,3	14	12,7	11,2														47
I 50-125A	015116	5,5	9,9					25	24,9	24,8	24,6	24,4	24,2	23,8	23,5	23,1	22,7	21,8	20,8	19,6	10,1	16,5														50
I 50-160B	015020	7,5	11,6							30,5	30,3	30,1	29,8	29,5	29	28,5	28	26,7	25,1	23,3	21,3	19,1	16,8													65
I 50-160A	015118	10	15,8							37	36,9	36,8	36,6	36,4	36,1	35,6	35,1	34	32,6	31	29,1	26,9	24,5													71
I 50-200C	015022	12,5	18,5								45,7	45,1	44,5	43,7	42,9	42	40,2	38,5	35,9	33	29	24,5														82
I 50-200B	015120	15	21								51	50,5	50	49,3	48,5	47,7	46,8	44,7	42,2	39,5	35,9	32														89
I 50-200A	015024	20	27								58,1	58	57,5	57	56,4	55,7	55	53,2	51,3	49	46,3	42,8	38,8													122
I 50-250C	015122	20	30,5									70,8	70,3	69,7	69	68,3	67,6	66	64	61,5	58,6	55	50,5													125
I 50-250B	015026	25	41,5									78	77,4	76,8	76,1	75,3	74,5	72,8	70,6	68,2	65,5	62,2	58,3													140
I 50-250A	015124	30	51,5									89,5	88,8	88,3	87,7	86,9	86,1	84,5	82,7	80,5	78	75,2	71,7													149
K 65-125B	015028	7,5	12,3										21	20,8	20,7	20,6	20,5	20,4	20,1	19,7	19,3	18,8	18,3	17,7	16,1	14,3	12,3									64
K 65-125A	015126	10	15,9										24,8	24,7	24,6	24,5	24,4	24,3	24,1	23,9	23,7	23,4	22,8	22,3	20,9	19,4	17,5	15								70
K 65-160C	015030	12,5	19,5														31,2	31,1	30,8	30,5	30,1	29,6	29	28,3	26,6	24,6	22,1	19,3	16							84
K 65-160B	015128	15	22,5														34,6	34,4	34,2	34	33,7	33,3	32,8	32,1	30,6	28,8	26,7	24,1	21,1							90
K 65-160A	015032	20	30														40,6	40,6	40,4	40,2	40	39,7	39,4	38,9	37,7	36,2	34,3	32,2	29,8							120
K 65-200C	015130	20	32																44,8	44,5	44,1	43,7	43	42,3	40,5	38	35,3	32								122
K 65-200B	015034	25	41,5																49,5	49,3	49	48,5	48	47,3	45,5	43,5	41	38								138
K 65-200A	015132	30	51,5																56,7	56,5	56,2	55,7	55,2	54,7	53,3	51,6	49,6	47,1	44							148
K 65-250B	015036	40	63,5																79,5	78,5	77,3	76	74,5	73	69,3	65	60	54,5	48,5							239
K 65-250A	015934	50	74,5																89,5	88,5	87,5	86,5	85,5	84	80,5	76,5	72	66,5	60,5	54						253
A 80-160D	015038	15	20,8																		25,6	25,3	25,1	24,7	23,9	22,9	21,8	20,6	19,3	17,9	16,3	14,6				98
A 80-160C	015136	20	25,8																		29,6	29,3	29	28,7	28,1	27	25,9	24,7	23,4	22	20,4	18,7	16,4			129
A 80-160B	015140	25	35																		34,1	33,9	33,7	33,4	32,7	32	31	30	29	27,7	26,4	25	22,9	20,3		143
A 80-160A	015138	30	42																			37,9	37,7	37,3	36,9	36,2	35,5	34,5	33,5	32,4	31,2	29,9	28	25,8	22,9		152
A 80-200B	015042	40	63,5																					50,8	50,6	50,3	49,8	49,3	48,6	47,7	46,7	45,5	44,8	41,6	38,6		233
A 80-200A	015140	50	74,5																						59,6	59,2	58,6	58	57,3	56,4	55,5	54,3	52,7	50,8	48,5	46,1	247

Características:
Electrobombas centrífugas normalizadas monobloc, construidas bajo norma UNI 7467 DIN 24255, cuerpo, soporte y turbina fundición gris, eje en acero INOXIDABLE (sello mecánico). Motor cerrado, protección IP-44. 50Hz-2.850 r.p.m.
Alimentación trifásica 220/380V y 380/660V para potencias superiores a 7,5 c.v.
Temperatura máxima del agua 90º C. Presión máxima 10 bar.

Characteristic:
Normalized centrifugal electric-pump monobloc, they are built under norm UNI 7467 DIN24255. Body, support and impeller smelting Grey.Axis in stainless steel (mechanical seal). Closed motor, protection IP-44, 50HZ - 2850 r.p.m.
Feed 3-phases 220/380V and 380/660 for powers superior 7,5CV.
Maximum temperature of the water 90º C. Pressure maximum 10 bar.